



Electric Disability Vehicle

Find a huge selection of Electric Disability Vehicle, Electric Moke, Electric Car Pony from China at Hilima Company. Its products are well-known at home and abroad for their durability and excellent performance. We hope to establish friendly cooperative relationship with your company with high quality products, reasonable price, considerate service and create a better future hand in hand.

1. Product introduction of the ELECTRIC DISABILITY VEHICLE

Design Concept: A disabled person sitting in a wheelchair does not need any third party assistance with only a remote control in the hand to achieve complete freedom of travel.

- ·All chassis and body are aluminum manganese alloy lightweight design.
- ·the Electric disabled vehicle has been certified by the EEC of the European Union and DOT of the United States
- •The first generation of products is open design, broad vision, sightseeing, relaxation functions. The second generation of products for closed, equipped with heater, air conditioning, greatly improve the comfort. The third generation of the product is intelligent voice control unmanned driving

Tel: +86-13969325101 E-mail: zlh7611@hotmail.com

E-mail: zlh7611@hotmail.com



· Electromagnetic hydraulic automatic lifting floor design, greatly convenient for disabled people up and down the wheelchair. The disabled can easily get on and off the vehicle in a wheelchair

2. Product parameter of electric disabled vehicle


Dimension	
L*W*H	2416mm×1385mm×1743mm
Wheelbase	1560 mm
Track Width (f/r)	1236mm
Mi. ground clearance	120mm
Min. turning diameter	9m
Wheel type(front/rear)	145/70R12
Max climbing capability	20%

3. Product feature and application of the electric disabled vehicle

Tel: +86-13969325101







The speed is 20km/h, safe and stable, and the endurance is 80km,

Which greatly expands the activity range of the disabled. *

Making it easy for the disabled to go shopping and sightseeing alone.*

Electromagnetic hydraulic automatic lifting floor design, expression of the expressi

Detailed parameters

Power System		
Motor	48V 3 kW	
Battery	12V-80Ah*4 lead-acid maintenance-free TROJAN battery	
Battery life	600 times recharging cycles	
Max speed	20 km/h	
Running distance	50kms	
Charging time	10hs	
Dimension		
L*W*H	2416mm×1385mm×1743mm	
Wheelbase	1560 mm	
Track Width (f/r)	1236mm	

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101 E-mail: zlh7611@hotmail.com



E-mail: zlh7611@hotmail.com



Mi. ground clearance	120mm
Min. turning diameter	9m
Wheel type(front/rear)	145/70R12
Max climbing capability	20%
Chassis System	
Braking system (F/R)	F: hydraulic disk /R: disk
Suspension System (F/R)	F: McPherson suspension/ R: independent suspension
Drive Type	Front Wheel driving
Function Specification	
Aluminum wheel rim	\vee
Manual rear view mirror	\checkmark
Colour options	Army green,White ,Black,Red,yellow
power steering	0
Heater	0

Tel: +86-13969325101













E-mail: zlh7611@hotmail.com